



ROUND SPACER



- ◆ MATERIAL: NYLON 66 (UL)/POM/PE/PC (UL)/ABS (UL)/PPS
- ◆ FLAME CLASS: 94V-2/94V-0/94HB
- ◆ COLOR: NATURAL/BLACK
- ◆ UNIT: mm



FOR 2.3-5, 2.3-5.5

PART NO	A(L)	B (ID)	C (OD)	PACKAGE	
0.7-1.6	1.6	0.7	2.0	1000	
0.7-3	3.0	0.71	2.2		
1.2-2.5	2.5	1.2	4.0		
1.2-3	3.0		3.2		
1.2-7.6	7.6		4.0		
1.4-3	3.0		1.4		3.5
1.7-11.3	11.3	1.7	3.0		
2.3-1.9	1.9	2.02	3.0		2000
2.05-3.5	3.5	2.05	3.0		1000
2.1-2.1	2.1	2.1	2.4		2000
2.2-2.5	1.5	2.2	2.5		
2.3-5	5.0	2.3	5.0	1000	
2.3-5.5	5.5				
2.4-9.4	9.4				2.4
2.5-2.15	2.15	2.5	4.0		
2.5-1655	16.0		5.5		
2.7-2.8	2.84	2.7	6.35		
2.7-6.7	6.71				
3.1-2.2	2.2	3.1	8.0		
3.1-3.5	3.5		5.7		
★ 3.1-4-6	4.0		6.0		
3.1-3.8	3.85	3.15	5.0		
3.1-4	4.0				
3.2-2.5	2.5	3.2	4.2	1000	
3.2-3	3.0		5.8		
3.2-4.45	4.45		6.4		
3-5.8	5.85		5.0		
3.2-6.4	6.4		5.8		
6432-6.4			6.4		
3.2-6.8	6.8		4.5		
★ 3.2-10	10.0		8.0		
3.35-5	5.0		3.35		8.0
★ 3.5-5.5	5.5		3.5		6.3
3.55-10	10.0	3.55	6.0		
3.6-19	19.0	3.6	8.0		
3.7-10	10.0	3.73	6.35		
3.9-5.3	5.3	3.9	8.0		
4.2-8.5	8.5	4.2	10.0		
4.4-6	6.0	4.4	7.43		
4.4-6.4	6.4		9.5		
4.5-3.2	3.18	4.45	6.35		
4.5-2.75	2.75	4.5	6.0		
4.5-19.9	19.9		6.1	250	
4.7-3.5	3.5		4.7	6.0	
4.9-3	3.0	4.9	7.94	1000	
4.9-4.5	4.5				
4.9-11.5	11.5				
4.9-13	13.0				
5-3.5	3.5				5.0
5-6.5L	6.5	9.5			
5-7.9L	7.9	9.5			

PART NO	A(L)	B (ID)	C (OD)	PACKAGE		
5-40	40.0	5.0	9.0	500		
★ 5.1-12.7	12.7	5.1	9.5	1000		
5.2-2.3	2.3	5.2	6.8	1000		
5.2-3	3.0					
5.2-4.1	4.1					
5.2-7.5	7.5		7.6			
5.2-11	11.0					
5.2-13	13.0		6.8			
5.4-122	122.0		5.4		9.53	250
5.5-4	4.0		5.5		15.0	1000
5.55-11.8	11.8		5.55		7.0	
5-5	5.0		5.6		8.6	
5-6	6.0					
5-7.9	7.9					
5-8	8.0					
5-8.8	8.8					
5-11.8	11.8					
5-14	14.0					
5-16.5	16.5					
5-16.7	16.7					
5-17	17.0					
5-20	20.0	5.7	7.7	250		
5.7-12.9	12.9					
5.7-14.1	14.1					
6-6	6.0	6.0	10.0	1000		
6.2-6S	6.0	6.2	10.0			
6.2-12	12.0		10.4			
6.3-20	20.0	6.3	12.7	250		
★ 6.4-3	3.0	6.4	12.0	1000		
6.5-3	3.0	6.5	9.2			
6-4.2	4.2	6.6	10.6			
6-4.8	4.8		9.1			
6-16	15.7					
6.8-5	5.0	6.8	10.0			
★ 6.9-12.7	12.7	6.9	12.7			
7-5.5	5.5	7.0	13.0			
7-8.7	8.7		10.0			
7.5-8.9	8.9	7.5	10.0			
7.5-29	29.0		11.0	250		
8-16	15.7		8.1	10.7		
★ 8.4-5	5.0	8.4	16.0	1000		
8.5-4.6	4.6	8.5	10.3			
8.5-612	6.0		12.0			
8.5-8	7.9		11.0			
9.1-7.5	7.5	9.1	17.9			
★ 9.25-4	4.0	9.25	12.25			
1012-26	26.0	10.0	12.0		250	
12.8-35	35.0	12.8	22.0		1000	
20.5-9.5	9.5	20.5	25.5			
29-16	16.0	29.5	33.5			

