



WIRE MOUNT

- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: NATURAL/BLACK
- ◆ UNIT: mm





HOLE: ØG
THICKNESS: T



PART NO	A	B	C	D	G	J	T	PACKAGE
MWCA-1	15.0	12.0	9.5	19.5	6.3~7.0	7.6	0.6~3.0	1000

WIRE MOUNT

- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: NATURAL/BLACK
- ◆ UNIT: mm



CHASSIS: ØG
THICKNESS: T
FOR CH-10, CH19





CHASSIS: ØG
THICKNESS: T
FOR CH-11, CH13

PART NO	A	B	C	D	E	G	J	T	PACKAGE
CH-10	14.8	10.8	5.4	15.9	11.2	4.8~5.0	5.2	0.5~2.0	
CH-11	14.8	10.8	5.4	15.9	11.1	4.8	2.4	0.8~1.6	500
CH-13	14.8	10.8	5.4	20.6	15.8	4.8	2.4	0.8~1.6	
CH-19	14.8	10.8	5.4	25.2	20.5	4.8~5.0	5.2	0.5~2.0	

WIRE MOUNT

- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: NATURAL/BLACK
- ◆ UNIT: mm



CHASSIS: ØG
THICKNESS: T

PART NO	A	B	C	D	E	G	J	T	PACKAGE
CH-14	15.0	11.2	5.5	16.6	11.9	4.8	5.2	0.8~1.8	500

