




STRAIN RELIEF BUSHING

- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: BLACK
- ◆ UNIT: mm






MOUNTING HOLE

ROUND TYPE


| PART NO | WILL FIT THESE CABLE | CHASSIS DIMENSION | | CHASSIS THICKNESS | DIMENSION | | | SECTION SHAPE | PACKAGE |
|---------|----------------------|-------------------|-----|-------------------|-----------|------|-----|---------------|---------|
| | SIZE | A | B | F | C | D | E | | |
| 2P-1 | Ø3.0-4.7 | 9.5 | 8.4 | 0.8~1.6 | 10.4 | 10.4 | 4.0 | ROUND TYPE | 500 |

STRAIN RELIEF BUSHING

- ◆ MATERIAL: NYLON 66 (UL)
- ◆ FLAME CLASS: 94V-2/94V-0
- ◆ COLOR: BLACK
- ◆ UNIT: mm



MOUNTING HOLE



FLAT TYPE

ROUND TYPE

| PART NO | WILL FIT THESE CABLE | | | CHASSIS DIMENSION | | CHASSIS THICKNESS MAX. | DIMENSION | | | SECTION SHAPE | PACKAGE |
|---------|----------------------|---------------|-----------|-------------------|------|------------------------|-----------|------|-----|---------------|---------|
| | UL TYPE DESIGNATION | AWG CONDUCTOR | SIZE | A | B | F | C | D | E | | |
| 2P-4 | SPT-1 | 18/2C | 3X5.6 | 9.5 | 8.7 | 1.6 | 10.4 | 10.4 | 4.0 | FLAT TYPE | 1000 |
| 3P-4 | SPT-1 | 18/2C | 3X5.6 | 11.0 | 9.9 | 1.6 | 11.5 | 10.4 | 4.0 | | |
| 3W-1 | SPT-1 | 18/2C | 3X5.6 | 11.0 | 9.9 | 2.5 | 11.5 | 10.4 | 4.0 | | |
| 4N-4 | SPT-2 | 18/2C | 3.7 | 12.7 | 11.8 | 1.6 | 13.3 | 10.4 | 4.0 | | |
| | | 16/2C | 3.8X7.6 | 13.1 | | | | | | | |
| 4K-4 | SPT-2 | 18/2C | 3.7 | 12.7 | 11.8 | 2.5 | 13.3 | 10.5 | 4.0 | | |
| | | 16/2C | 3.8X7.6 | 13.1 | | | | | | | |
| 5N-4 | SVT | 18/3C | Ø6.4-7.4 | 12.7 | 11.5 | 1.6 | 13.5 | 10.9 | 4.2 | | |
| | | | | 13.1 | | | | | | | |
| 5P-4 | SVT | 18/3C | Ø6.4-7.4 | 12.7 | 11.5 | 2.5 | 13.5 | 10.9 | 4.2 | | |
| | | | | 13.1 | | | | | | | |
| 6N-4 | SJT | 18/3C | Ø7.6 | 15.9 | 14.0 | 1.6 | 16.8 | 14.8 | 5.6 | ROUND TYPE | 500 |
| 6P-4 | SJT | 18/3C | Ø7.6 | 15.9 | 14.0 | 3.2 | 16.8 | 14.8 | 5.6 | | |
| 6N3-4 | SJT | 16/3C | Ø8.2-9.2 | 15.9 | 14.0 | 1.6 | 16.2 | 15.0 | 5.6 | | |
| 6P3-4 | SJT | 16/3C | Ø8.2-9.2 | 15.9 | 14.0 | 3.2 | 16.2 | 14.8 | 5.7 | | |
| 7N-2 | SJT | 14/3C | Ø9.2-10.5 | 19.0 | 16.5 | 1.6 | 19.5 | 19.1 | 7.8 | | |
| | | | Ø11.0 | 19.8 | | | | | | | |
| 7P-2 | SJT | 14/3C | Ø9.2-10.5 | 19.0 | 16.5 | 3.2 | 19.5 | 19.4 | 7.8 | | |
| | | | Ø11.0 | 19.8 | | | | | | | |

