

▶ TERMINAL BLOCK

PCB Terminal block (carrello)



TOPTTEK®
HARDWARE ELECTRONIC COMPONENTS



www.toptek-co.com

SPECIFICATION MODEL KF104 P.5.08 :

| | | |
|----|-----------------------|--|
| 1 | Screw Material | M3.0 steel, Zinc plated, "-" slot type |
| 2 | Housing Material | PA66, UL94V-0 |
| 3 | Clamp Material | Brass, Ni plated |
| 4 | Pin Header Material | Brass, Tin plated |
| 5 | Rated voltage | UL: 300V IEC:250V |
| 6 | Rated Current | UL: 15A IEC: 24A |
| 7 | Insulation Resistance | 500MΩ / DC500V |
| 8 | Withstanding Voltage | AC2000V / 1min |
| 9 | Wire Range | 24-14AWG 2.5mm ² |
| 10 | Operating Temperature | -40°C.....+105°C |
| 11 | Soldering Temperature | 250°C ± 5 / 5sec |
| 12 | Torque | 0.5N.m (4.43Lb.in) |
| 13 | Strip Length | 6-7mm |



▶ ORDER INFORMATION

K F 1 0 4 - 5.08 X X P

Pitch:mm
No. of Poles
2~24P

